Water Curb

Contains, Controls & Diverts Water



- Fill & drain with water as needed
- ♦ Compact & lightweight
- Store empty & fill on site as needed
- Dual chambers prevent rolling out of position
- Durable & chemical resistant 10mil polyurethane
- Reusable year after year
- Use for doorways, garages & more!
- Flood protection for up to 6.5in or 10in



Instructions

Place it & fill it. It's really that easy!



1. Lay in desired location. Note: Once filled they can be heavy and difficult to move.



2. Remove cap, insert hose & turn on water.



3. When filled to desired height, remove hose, try to guide air pockets to opening, squeeze down & then replace cap. Note: In freezing weather, fill 2/3 full.



4. To drain, remove cap & lift opposite end of curb to the spout. Be sure water drains away from property.




5. Store away for later.





6.5in (16.5cm) PROTECTION HEIGHT				
Length	Weight-Empty	Weight-Filled	Holds	Part #
5in (1.5m)	2lbs (.9kg)	320lbs (145kg)	40gal (151 l)	QDWC65
10in (3m)	3lbs (1.4kg)	640lbs (290kg)	80gal (302 l)	QDWC610
20in (6m)	4lbs (1.8kg)	1,280lbs (580kg)	160gal (605 l)	QDWC620
10in (25.4cm) PROTECTION HEIGHT				
5in (1.5m)	4lbs (1.8kg)	1,400lbs (635kg)	175gal (663 l)	QDWC105
10in (3m)	8lbs (3.6kg)	2,800lbs (1,270kg)	350gal (1,325 l)	QDWC1010
20in (6m)	16lbs (7.3kg)	5,600lbs (2,540kg)	700gal (2,650 l)	QDWC1020



Drain Time: 8 - 20gal (30-75 l) per minute





EDWOSB Certified FEMA Registered

Patent Pending





PHONE 0800-478-784

Email: steven@survive-it.co.nz

Visit: www.dspa.nz for more info